

Timestep T

- Hardwearing, homogeneous sheet
- *Marbleized Grey and Solid Black, Specialized colors available call for more info*

SPECIFICATION



1.5mm
.06 in



N/A



N/A



Timestep T
2m x 27.5m
6.56ft x 90ft



2.36kg/m²
4.34lbs/yd²



GENERAL PERFORMANCE

EN 649

ASTM F1913

ASTM F1700

Agrément – 1.5mm: G3ws

1.5mm



REACTION TO FIRE

EN 13501-1 Class Bfl-S1

ASTM E662 <450

ASTM E648 Class 1⁺

{ EN ISO 9239-1 ≥8kw/m² (all gauges)
EN ISO 11925-2 Pass (all gauges)



SLIP RESISTANCE

EN 13893 Class DS

AS/NZS 4586 R9



ABRASION RESISTANCE

EN 649 Group M



MARITIME USAGE

NOT SUITABLE



HYGIENE

This product has been independently tested and results demonstrate that it inhibits the growth of MRSA. An effective cleaning regime is however, the most important defence against infection.



ELECTRICAL BEHAVIOUR (body voltage)

EN 1815 This product does not accumulate static charges above 2kV and is classified as 'antistatic'.



ENVIRONMENT

BRE Green Guide to Specifications A rating

Recyclable material



APPLICATIONS

Timestep T when used with a sprung subfloor is a lightweight multipurpose dance surface. It is ideally suited for touring and uses on stage.



For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance,

Call 800-523-0960



Stagestep Inc. 4701 Bath St #46, Philadelphia Pa 19137
215-636-9000 800-523-0960
www.stagestep.com

TIMESTEP T

HOMOGENOUS

PERFORMANCE AND PROPERTIES